

ZENON

NEO

SAE 0W-30

**SYNTHETIC
SEMI SYNTHETIC**

API SN/CF
ACEA A3/B4

DESCRIPTION

ZENON NEO 0W-30 is an ultra-low Viscosity Synthetic Engine oil developed for modern Gasoline engines. Its advanced formulation enhances Engine efficiency, improves fuel efficiency, and delivers outstanding overall protection. With superior wear resistance, excellent film stability, and deposit control under all operating conditions, ZENON NEO 0W-30 is especially recommended for vehicles equipped with start/stop.

ENVIRONMENTAL CARE

Dispose of used oil responsibly at authorized collection points.

- Do not release into drains, soil, or water.
- Follow local environmental regulations.

STORAGE RECOMMENDATIONS

Store indoors, under cover, in a cool and dry location.

- Avoid prolonged exposure to direct sunlight, freezing conditions, or storage above 60°C.
- Keep containers properly sealed when not in use.

HEALTH & SAFETY

Avoid prolonged or repeated contact with used oil.

- Wash skin thoroughly with soap and water after handling.
- Refer to the Material Safety Data Sheet (MSDS) on our website for full safety information.

TYPICAL PROPERTIES

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	11.5
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-36

BENEFITS

Exceptional protection against wear, sludge, and harmful deposits

- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions



APPLICATIONS

Recommended for modern Gasoline and Diesel passenger vehicles.

- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

