

ZENON

SAE 25W-60

ENGINE OIL

| API CF

DESCRIPTION

ZENON 25W-60 is a Mineral engine oil specially formulated to deliver exceptional protection for engines operating under extreme temperature conditions. Its extra-thick oil film provides outstanding wear resistance, minimizes oil consumption, and ensures stable lubrication in high-stress environments. It is ideal for older, high mileage Diesel engines, motorcycles, and performance vehicles requiring maximum protection.

BENEFITS

- Extra-strong lubricating film for maximum wear protection
 - Excellent resistance to high-temperature oxidation and oil breakdown
 - Reduces oil consumption in older and high-mileage engines
 - Protects against deposits, sludge, and varnish build-up
- Ensures reliable performance in severe driving and extreme climates



ENVIRONMENTAL CARE

Dispose of used oil responsibly at authorized collection points.

- Do not release into drains, soil, or water.
- Follow local environmental regulations.

HEALTH & SAFETY

Avoid prolonged or repeated contact with used oil.

- Wash skin thoroughly with soap and water after handling.
- Refer to the Material Safety Data Sheet (MSDS) on our website for full safety information.

STORAGE RECOMMENDATIONS

Store indoors under cover whenever possible.

- Avoid temperatures above 60°C, direct sunlight, or freezing conditions.
- Ensure containers are tightly sealed when not in use.

TYPICAL PROPERTIES

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.885
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	25.6
Viscosity Index	ASTM D2270	-	120
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-24

APPLICATIONS

High-mileage Diesel engines require 25W-60.

- Older vehicles with higher oil consumption.
- Motorcycles and performance engines operate under severe conditions.
- Ideal for hot climates, high loads, and extended driving.

