

FULLY SYNTHETIC

API SP/CK-4
ACEA A3/B4

DESCRIPTION

ZENON PRO 5W-40 is a fuel-efficient fully Synthetic Engine Oil formulated with advanced technology for modern Gasoline and high-performance light-duty Diesel Engines. It is suitable for engines with or without turbochargers, providing superior wear protection. This Motor oil is suitable for Vehicles including turbocharged, multi-valve, fuel-injected, LPG, NGV, and naturally aspirated Gasoline and Diesel engines.

BENEFITS

- Exceptional protection against wear, sludge, and harmful deposits
- Enhances fuel efficiency while reducing CO₂ and other emissions
- Fast lubrication during cold starts for immediate engine safety
- Long-lasting protection under both city and highway driving conditions

ENVIRONMENTAL CARE

Dispose of used oil responsibly at authorized collection points.

- Do not release into drains, soil, or water.
- Follow local environmental regulations.

STORAGE RECOMMENDATIONS

Store indoors, under cover, in a cool and dry location.

- Avoid prolonged exposure to direct sunlight, freezing conditions, or storage above 60°C.
- Keep containers properly sealed when not in use.

HEALTH & SAFETY

Avoid prolonged or repeated contact with used oil.

- Wash skin thoroughly with soap and water after handling.
- Refer to the Material Safety Data Sheet (MSDS) on our website for full safety information.

TYPICAL PROPERTIES

Specification	Test method	Unit	Result
Density 15°C/60°F	ASTM D1298	Kg/L	0.870
Kinematic Viscosity @ 40°C	ASTM D445	CSt	TBR
Kinematic Viscosity @ 100°C	ASTM D445	CSt	14.2
Viscosity Index	ASTM D2270	-	150
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-33



APPLICATIONS

Recommended for modern Gasoline and Diesel passenger vehicles.

- Particularly suitable for engines requiring low-viscosity, Fuel-efficient lubricants.

